



2023 7 TAIKAI



Oil Pattern Distance	43	Reverse Brush Drop	37	Oil Per Board	40 ul
Forward Oil Total	10.6 mL	Reverse Oil Total	8.88 mL	Volume Oil Total	19.48 mL
Tank Configuration	N/A	Tank A Conditioner	FIRE	Tank B Conditioner	ICE

	START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	1	10	A	37	0.0	0.0	0.0	1480
2	3L	3R	1	10	A	35	0.0	1.4	1.4	1400
3	7L	7R	2	14	A	54	1.4	5.3	3.9	2160
4	9L	9R	2	18	A	46	5.3	10.4	5.1	1840
5	10L	10R	2	18	A	42	10.4	15.5	5.1	1680
6	12L	12R	3	22	A	51	15.5	24.8	9.3	2040
7	2L	2R	0	26	A	0	24.8	43.0	18.2	0

	START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	B	0	43.0	39.0	-4.0	0
2	14L	14R	2	26	B	26	39.0	31.7	-7.3	1040
3	13L	13R	2	26	B	30	31.7	24.4	-7.3	1200
4	12L	12R	3	22	B	51	24.4	15.1	-9.3	2040
5	11L	11R	2	18	B	38	15.1	10.0	-5.1	1520
6	9L	9R	1	14	B	23	10.0	8.1	-1.9	920
7	8L	8R	1	14	B	25	8.1	6.2	-1.9	1000
8	6L	6R	1	14	B	29	6.2	4.3	-1.9	1160
9	2L	2R	0	10	B	0	4.3	0.0	-4.3	0

Cleaner Ratio Main Mix NA Forward
Cleaner Ratio Back End Mix NA Reverse
Cleaner Ratio Back End Distance NA Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Item	3L-7L-18L-18R	8L-12L-18L-18R	13L-17L-18L-18R	18L-18R-17R-13R	18L-18R-12R-8R	18L-18R-7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle:Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	8.21	1.98	1.02	1.02	1.98	8.21

